

No one does it
like you

Canon

REAP THE BENEFITS OF PRODUCTIVITY, VERSATILITY, AND HIGH QUALITY

The imagePRESS C910 series is a true, light- to mid-volume production press that incorporates advanced technologies to help print establishments achieve amazing results—all in a small footprint.



imagePRESS C910/C810/C710

Incorporated into this colour digital press is Canon's passion and unique understanding of imaging, photography, colour science, and workflow. This expertise has resulted in a high-quality digital press that's both productive and versatile for printing establishments of varying shapes and sizes.



imagePRESS C910 shown with optional accessories.



OUTSTANDING PRODUCTIVITY

- Outstanding Productivity
- Production speeds of up to 90 ipm
- Maintains rated speed on uncoated stocks up to 220 gsm
- 7,650-sheet¹ feeding capacity with up to six different sources



AMAZING QUALITY

- 2400 × 2400-dpi print resolution utilizing the unique R-VCSEL imaging technology
- Intuitive calibration process that uses internal sensors to measure test patches
- Translucent CV Toner produces vibrant images on a wide variety of stocks
- Multi D.A.T. helps to achieve consistent colour across long runs automatically



BRILLIANT VERSATILITY

- Support stocks up to 350 gsm
- Runs a variety of envelopes and long sheets up to 1300 mm
- Helps achieve highly accurate and consistent registration, even on large and heavy stocks
- Coated support from 85 gsm

imagePRESS C910 Series SPECIFICATIONS

Main Engine

Technology	Electrophotography		
Resolution	Up to 2400 × 2400 dpi		
Halftones	256-Level Grayscale		
Print Speed	(Simplex/Duplex)		
	imagePRESS C910	imagePRESS C810	imagePRESS C710
8.5" × 11"	Up to 90 ipm	Up to 90 ipm	Up to 70 ipm
11" × 17"	Up to 45 ipm	Up to 40 ipm	Up to 35 ipm
12" × 18"	Up to 42 ipm	Up to 35 ipm	Up to 35 ipm
13" × 19"	Up to 40 ipm	Up to 38 ipm	Up to 33 ipm
13" × 30"	Up to 23 ipm	Up to 22 ipm	Up to 19 ipm
Paper Size	100 × 148 mm to 330 × 488 mm (3.94" × 5.83")		
Paper Feeding	Standard: Up to 1,650 Sheets(80 gsm) Maximum: Up to 7,650 Sheets(80 gsm)		
Paper Weight	52 gsm to 350 gsm		
Envelopes:**	ISO-C5, COM 10, Monarch, DL 6" × 9", 9" × 12", 10" × 13"		
Duplexing/Perfecting	Automatic Duplex/perfect (Any supported stock except envelopes)		
Power Source	Single-Phase 2 × 240 V/15 A		
Dimensions(H × W × D)	1424 mm × 1530 mm × 934 mm (Includes Operator Panel)		
Cassette(Upper)			
Paper Capacity	680/80 Sheets(64 gsm) 550/50 Sheets(80 gsm)		
Paper Size	Universal cassette: A3, B4R, A4RR, A4R, B5S, B5L, A5S, SRA3, 11" × 17"S, LGLS, LTRL, LTRS, STMTS, E × E_L, 12" × 18"S, 13" × 19"S, 8KS, 16KL, 16K, Postcard(Postcard, Round-trip postcard, 4R-up postcard), (2, 3, 3, COM10, Monarch, DL, ISO-C5, (6" × 9", 9" × 12", 10" × 13")), (2/C5/9" × 12"/10" × 13") Envelope(COM10, Monarch, DL, ISO-C5, Custom(6" × 9", 9" × 12", 10" × 13")), Envelop kit required(C5/9" × 12"/10" × 13" don't need kit), Custom(100.0 × 148.0 mm–330.2 × 487.7 mm)		
Dimensions(H × W × D)	Included in main unit		
Cassette(Middle)			
Paper Capacity	680/80 Sheets(64 gsm) 550/50 Sheets(80 gsm)		
Paper Size	Universal cassette: A3, B4R, A4RR, A4R, B5S, B5R, A5S, SRA3, 11" × 17"S, LGL, LTRR, LTR, STMT, E × E_L, 12" × 18"S, 13" × 19"S, 8KS, 16KL, 16K, Postcard(Postcard, Round-trip postcard, 4R-up postcard), (2, 3, 3, COM10, Monarch, DL, ISO-C5, (6" × 9", 9" × 12", 10" × 13")), (2/C5/9" × 12"/10" × 13")/Envelope(COM10, Monarch, DL, ISO-C5, Custom(6" × 9", 9" × 12", 10" × 13")), Envelop kit required(C5/9" × 12"/10" × 13" don't need kit), Custom(100.0 × 148.0 mm–330.2 × 487.7 mm)		
Dimensions(H × W × D)	Included in main unit		
Power Source	Included in main unit		
Cassette(Lower)			
Paper Capacity	680/80 Sheets(64 gsm) 550/50 Sheets(80 gsm)		
Paper Size	Universal cassette: A3, B4R, A4RR, A4R, B5, B5R, A5S, SRA3, 11" × 17", LGR, LTRR, LTR, STMT, E × E_R, 12" × 18", 13" × 19", 8K, 16KR, 16K Postcard(Postcard, Round-trip postcard, 4R-up postcard), (2, 3, 3, COM10, Monarch, DL, ISO-C5, (6" × 9", 9" × 12", 10" × 13")), (2/C5/9" × 12"/10" × 13")/Envelope(COM10, Monarch, DL, ISO-C5, Custom(6" × 9", 9" × 12", 10" × 13")), Envelop kit required(C5/9" × 12"/10" × 13" don't need kit), Custom(100.0 × 148.0 mm–330.2 × 487.7 mm)		
Dimensions(H × W × D)	Included in main unit		
Power Source	Included in main unit		
Duplexing Through Path/Stackless			
Paper Capacity	A3, B4R, A4RR, A4R, B5S, B5L, A5S, 11" × 17"S, LGLS, LTRL, LTRS, E × E_L, STMTS, SRA3, 12" × 18", 13" × 19", 8K, 16KR, 16K, Postcard(Postcard, Round-trip postcard, 4R-up postcard), Custom(100.0 × 148.0 mm–330.2 × 487.7 mm)		
Dimensions(H × W × D)	Included in main unit		
Power Supply	Included in main unit		
Input Accessories			
Stack Bypass			
Paper Capacity	250 Sheets(80 gsm/64 gsm) 1 Sheet(Intrack>487.7 mm) Fed length>487.7 mm: Support by hands		
Paper Size	A3, B4R, A4RR, A4R, B5S, B5L, A5S, SRA3, 11" × 17"S, LGLS, LTRL, LTRS, E × E_L, STMTS, 12" × 18"S, 13" × 19"S, 8KS, 16KL, Postcard(Postcard, Round-trip postcard, 4R-up postcard), Envelope(COM10, Monarch, DL, ISO-C5, Custom(6" × 9", 9" × 12", 10" × 13")), Custom(100.0 × 148.0 mm–330.2 × 487.7 mm) Fed length>487.7 mm(Op/Long sheet tray required):210 × 487.8–330.2 × 1,300 mm		
Dimensions(H × W × D)	Refer to system size table		
Power Source			
Paper Capacity	680/80 Sheets(64 gsm) 550/50 Sheets(80 gsm)		
Paper Size	Universal cassette: A3, B4R, A4RR, B5, B5R, A5, SRA3, 11" × 17", LGL, LTRR, STMT, E × E_R, 12" × 18"S, 13" × 19"S, 8K, 16KR, 16K Postcard(Postcard, Round-trip postcard, 4R-up postcard), (2, 3, 3, COM10, Monarch, DL, ISO-C5, (6" × 9", 9" × 12", 10" × 13")), (2/C5/9" × 12"/10" × 13")/Envelope(COM10, Monarch, DL, ISO-C5, Custom(6" × 9", 9" × 12", 10" × 13")), Envelop kit required(C5/9" × 12"/10" × 13" don't need kit), Custom(100.0 × 148.0 mm–330.2 × 487.7 mm)		
Dimensions(H × W × D)	Included in main unit		
Power Source			

POD Deck Lite-C1	
Paper Capacity	3,500 Sheets(80 gsm)
Paper Size	Universal deck by user's operation: A3, B4R, A4RR, A4R, B5S, B5R, A5S, SRA3, 11" × 17", LGL, LTRR, LTR, E × E_R, STMT, 12" × 18"S, 13" × 19", 8K, 16KR, 16K, Postcard(Postcard, Round-trip postcard, 4R-up postcard; JP only), (2, 3, 3, COM10, Monarch, DL, ISO-C5, (6" × 9", 9" × 12", 10" × 13")), (10" × 13") Envelope(COM10, Monarch, DL, ISO-C5, Custom(6" × 9", 9" × 12", 10" × 13")), Envelop kit required(10" × 13" don't need kit), Custom(139.7 × 148.0 mm–330.2 × 487.7 mm)
Dimensions(H × W × D)	717 × 686 × 574 mm(Including buffer)
Power Source	220–240 V AC, 50/60 Hz, 1.2 A
Multi-Drawer Deck-C1	
Paper Capacity	2,000 Sheets(80 gsm) × 3
Paper Size	Universal deck by user's operation: A3, B4R, A4RR, A4R, B5S, B5L, A5S, SRA3, 11" × 17", LGR, LTRR, LTR, E × E_R, STMT, 12" × 18"S, 13" × 19"S, 8K, 16K, 16K, Envelope(ISO-C5; EU only), Custom(139.7 × 182 mm–330.2 × 487.7 mm)
Dimensions(H × W × D)	155 kg
Power Source	220–240 V AC, 50/60 Hz, 1.7 A
Pop Deck Lite XL-A1	
Paper Capacity	<=19.2" 3,500 Sheets(80 gsm) >19.2" 1,000 Sheets(80 gsm)
Paper Size	Universal deck by user's operation: A3, B4R, A4RR, A4R, B5S, B5L, A5S, SRA3, 11" × 17", LGL, LTRR, LTR, E × E_R, STMTS, 12" × 18", 13" × 19", 8K, 16KR, 16K, Postcard(Postcard, Round-trip postcard, 4R-up postcard; JP only), (2, 3, 3, COM10, Monarch, DL, ISO-C5, (6" × 9", 9" × 12", 10" × 13")), (10" × 13")/Envelope(COM10, Monarch, DL, ISO-C5, Custom(6" × 9", 9" × 12", 10" × 13")), Envelop kit required(10" × 13" don't need kit), Custom(139.7 × 148.0 mm–330.2 × 487.7 mm, 210.0 × 487.8–330.2 × 762.0 mm)
Dimensions(H × W × D)	1,105 × 686 × 574 mm(Including buffer)
Power Source	AC 100 V 2.4 A 50/60 Hz(JPN) 120–127 V AC 60 Hz, 2.2 A(US) 220–240 V AC, 50/60 Hz, 1.2 A(EU)
Finishing Accessories	
Staple/Booklet Finisher W1-Pro	
Tray Capacity	
Top Tray	Plain Paper: 52–350 gsm, Coated Paper: 85–350 gsm
Lower Tray	Plain Paper: 52–350 gsm, Coated Paper: 85–350 gsm
Saddle-Stitch Tray	
Dimensions(H × W × D)	800 × 792 × 1239 mm 1,136 × 792 × 1,239 mm(w. Long sheet tray)
Power Source	AC 100 V 10 A–50/60 Hz(JPN), AC 120–240 V 8 A–50/60 Hz(US), AC 220–240 V 8 A–50/60 Hz(EU), AC 220–240 V 8 A–50/60 Hz(AP)
Staple Positions	2 Positions(Center standard, Fixed pitch)
Paper Weight	Cover sheet: 64–300 gsm, Body sheet: 52–220 gsm
Paper Size	A3, B4R, A4R, 11" × 17"S, LTR, LGL, 12" × 18", SRA3, 13" × 19", Custom Size(210 × 279.4–330.2 × 487.7 mm(13" × 19.2"))
Stapling Capacity	Plain Paper: 2–25 Sheets(52–63.9 gsm), 2–25 Sheets(64–80 gsm), 2–15 Sheets(80.1–105 gsm), 2–5 Sheets(105.1–209 gsm), 2–4 Sheets(209.1–220 gsm) including cover sheet Coated Paper: 2–10 Sheets(100–128 gsm), 2–5 Sheets(128.1–209 gsm), 2–4 Sheets(209.1–220 gsm) including cover sheet *All numbers include one cover page which has same weight paper. Staple capacity depends on substrate weight, thickness, kinds etc. Number of body papers may decrease by substrate. Instead of making limitation, specification is managed by media guide
Booklet Stapling Capacity(80 gsm)	
Uncoated	
Coated	
V-Folding	
Multi-Function Professional Puncher-A1	
Paper Size	Bypass: 100 × 148 mm–330.2 × 1,300 mm Punch: SRA3, A3, SRA4RR, SRA4R, A4RR, A4R, 12" × 18"S, 11" × 17", LGL, LTRR, LTR, 9" × 12", 9" × 12", Index Crease: SRA3, A3, A4R, 12" × 18", 11" × 17", LGR, LTR, 12.6" × 19.2", 13" × 19", 13" × 19.2"
Paper Weight	Punch: Plain paper 75–300 gsm, Coated paper 118–300 gsm Crease: Plain paper 157–300 gsm, Coated paper 157–300 gsm Through: Plain paper 75–350 gsm, Coated paper 118–350 gsm
Dimensions(W × D × H mm)	445 × 795 × 1040 mm
Power Supply	230 V/50 Hz/1.9 A
Document Inserter-N1	
Type	Independent inserter
Number of Insertion Tray	2 trays
Paper Feeding Method	Retard separation method
Paper Size	Insert path: A3, A4R, A4R, B4R, B5R, B5, SRA3, 11" × 17", 12" × 18", 13" × 19, LGL, LTRR, LTR, E × E_R, 8K, 16K/User change(182 × 182 mm–330.2 × 487.7 mm) Through path: All paper size engines supports
Capacity Detection	Yes
Capacity	200 × 2(80 gsm)
Dimensions(W × D × H mm)	336 × 793 × 1407 mm 746 × 793 × 1407 mm
Power Supply	AC 100–240 V, 1.0 A, 50/60 Hz

Paper Folding Unit-J2	
Folding Type	Z fold, Letter fold in(C fold), Letter fold out, Double Parallel fold, Half fold
Paper Size	Z fold: A4R, B4R, A3, LTR, LGR, 11" × 17" Letter fold in(C fold): A4R, LTR Letter fold out: A4R, LTR Double parallel fold: A4R, LTR, LGR Half fold: A4L, LTR
Dimensions(W × D × H mm)	336 × 793 × 1190 mm
Weight(kg)	71 kg
Power Source	From Finisher

High Capacity Stacker-H1	
Offset Stack Capacity	
Top Tray Capacity	
Paper Size	Stack tray: A5R(140 × 182 mm)–13" × 19.2"(330.2 × 487.7 mm) Escape tray(with Long sheet tray Op.): A5R(140 × 182 mm)–330.2 × 1,300 mm Through path: 140 × 182 mm–330.2 × 1,300 mm DFD/DFD path: 140 × 182 mm–330.2 × 762 mm
Paper Weight	Plain Paper=52–350 gsm, Coated Paper=100–350 gsm Through path: All substrates engines supports

Max. Connectivity	
Dimensions(H × W × D)	899 × 745 × 1040 mm(899 × 745 × 1141 mm; Including top tray part) 899 × 1250 × 1040 mm(when stack tray is ejected) (899 × 1250 × 1141 mm; Including top tray part)
Power Source	90 V–264 V, 47 Hz–63 Hz, 10 A

Perfect Binder-E1	
Cutting Method	
Finished Book Size	
Length	
Book Thickness	
Body Paper Weight	
Cover Paper Weight	
Trim Range	
Top/Bottom	
Side	
Dimensions(H × W × D)	(W)922 mm × (D)791 mm × (H)1300 mm
Power Source	AC 220–240 V, 50/60 Hz, 3.0 A

Booklet Trimmer-F1	
Margin Trimming	
Trim Amount	
Trim Thickness	
Paper Weight	Non-coated Paper: 52–300 gsm, Coated Paper: 100–300 gsm
Output Tray Capacity	Approx. 5,000 Sheets(Trim width=20 mm, A4R, 80 gsm)
Dimensions(H × W × D)	2,095 × 790 × 1,040 mm

Two Knife Trimmer-A1	
Margin Trimming	
Trim Amount	
Trim Thickness	
Paper Weight	Non-coated Paper: 52–300 gsm, Coated Paper: 100–300 gsm
Output Tray Capacity	750 Sheets for each side(Trim width=15 mm, A4R, 80 gsm) *Fold chip is counted as 1(1500 Sheets based on booklet sheet)
Dimensions(H × W × D)	536 × 770 × 1,040 mm

Staple/Booklet Finisher-AC1	
Tray Capacity	
Top Tray	
Lower Tray	
Saddle-Stitch Tray	
Staple Positions	
Paper Weight	
Paper Size	A3, B4R, A4R, 11" × 17"S, 12" × 18"S, LTRS, LGLS, (195 × 270 mm–304.8 × 457.2 mm)
Stapling Capacity	20(52–81.4 gsm)(256 gsm)/Max. 20 Sheets 52–81.4 gsm(including max. cover paper(256 gsm)) : 20(52–81.4 gsm), 10(82–105 gsm), 5(106–150 gsm), 4(151–209 gsm), 3(210–220 gsm)/Non coated paper: Up to 20 Sheets(52–81.4 gsm), Up to 10 Sheets(82–105 gsm), Up to 5 Sheets(106–150 gsm), Up to 4 Sheets(151–209 gsm), Up to 3 Sheets(210–220 gsm) : 5(85–150 gsm), 4(151–209 gsm), 3(210–220 gsm) *Including 1 cover page
Booklet Stapling Capacity(80 gsm)	2000 staples(special staples)
Dimensions(H × W × D)	
Power Source	Supply from main unit

Internal Puncher Unit-A1	
Paper Size	2/3/2/4R, 4R
Paper Weight	

Dimensions(W × D × H mm)	107 mm × 615 mm × 825 mm
Power Supply	Supply from main unit

Jogger kit-A1	
Paper Weight	Unsorted: 52"300 gsm Sorted: 52"256 gsm
Output Paper Size	Unsorted: A3, B4R, A4RR, A4R, B5L, B5S, 11 × 17S, LGLS, LTRL, LTRS, E × EL, 8KS, 16kL, 16kS Sorted : A3, B4R, A4RR, A4R, B5L, 11 × 17S, LGLS, LTRL, LTRS, E × EL, 8KS, 16kL
Shift Amount	232.1"297.0 mm: 20 mm A4: 17 mm LGLS/LTRS: 23 mm

DFD Adapter/Bridge	
Paper Size	388 × : 182 × 182 mm–330.2 × 487.7 mm
Paper Weight	Plain Paper=52–325 gsm, Coated Paper=128–325 gsm
Power Supply	90–264 V/47–63 Hz/more than 10 A
Dimensions(W × D × H mm)	Adapter: 300 × 745 × 1040 mm Bridge: 600 × 745 × 150 mm Space between wall and engine: 450 mm
Weight(kg)	Adapter: 60 kg Bridge: 30 kg

For information and services contact

Canon Australia Pty Ltd 1800 444 199 canon.com.au
Canon New Zealand Ltd 0800 222 666 canon.co.nz

No one does it like you

Canon