

XA35

COMPACT PROFESSIONAL FULL HD DV CAMERA

The XA35 is a compact professional-use Full HD video camera, which employs a newly developed Canon CMOS sensor making possible exceptional high-sensitivity imaging performance. The XA35 is ideally suited across a variety of shooting applications, from the capturing of news footage and other broadcasting content to the recording of documentaries and events.



HD-SDI Terminal

The XA35 is equipped with an HD-SDI terminal - the video signal can be routed from the camera through the HD-SDI terminal and streamed to a broadcast van directly. In addition, a recorder can be connected to make uncompressed video recordings for archiving purposes

Flexible Handling

The XA35 includes a detachable handle unit as standard which provides XLR Terminals (INPUT1/INPUT2), a microphone holder, high-level audio features and an infrared shooting feature

Outstanding imaging performance

Combining an newly developed Canon HD CMOS PRO sensor with an impressive 20x optical zoom lens & Canon's DIGIC DV 4 imaging platform, the XA35 achieves smooth, high-quality video with minimal noise, even when shooting in dimly lit environments.



no one sees it like you

Canon

XA35

COMPACT PROFESSIONAL FULL HD DV CAMERA



Newly developed Canon HD CMOS Pro Sensor featured a signal-to-noise improved by 3db & approx 40% reduction in noise compared to the previous model (XA20). This delivers exceptional high-sensitivity imaging performance



Highly versatile Canon HD Video lens combines a wide angle focal length of 26.8mm (35mm camera equivalent) together with powerful 20x zoom performance whilst maintaining a compact design



Featuring a newly developed DiGiC DV4 image processor, for optimum colour reproduction, faster AF speeds and improved image stabilization function



5-axis image stabilization delivers enhanced electronic correction of roll & tilt motions, reducing image distortion substantially even when shooting whilst walking



Highlight Priority mode facilitates the faithful expression of tonal gradations, colours and sharpness in the mid- to high-brightness range delivering an effect similar to HDR



Wide DR Gamma compresses high brightness areas seamlessly and delivers an expanded dynamic range of 600%

no one sees it like you

Canon

Technical Specifications

XA35

IMAGE SENSOR	
Sensor	1/2.84 type HD CMOS Pro
System	RGB primary colour filter
Total pixels per sensor	Approx. 3.09 megapixels
Effective pixels per sensor	Approx. 2.91 megapixels (2136 x 1362)
Minimum Illumination (PAL Version)	Auto: 1.0 lux With Auto Slow Shutter selected Low Light Mode: 0.1 lux
Horizontal Resolution	900 TV lines at highest image quality
LENS	
Zoom ratio	20x
Focal length	26.8 - 576mm (35mm equivalent / 28.8-576mm with Dynamic IS on)
Minimum focus distance	60cm (throughout zoom range); 10mm (wide angle)
ND filter	Built-in gradation filter (Auto or Off)
Zoom control	Zoom rockers on body and handle; Selectable manual zoom/focus ring on lens; Selectable High Speed and Soft Zoom modes available Variable (body rocker only) or Constant speed (body and handle rocker; Fast/Normal/Slow, 16 speed level settings in each)
Zoom speed	MANUAL: Lens ring, Touchscreen OLED (touch Focus, Touch and Track), Focus Preset AUTO: Face Priority AF / Face Only AF / Instant AF / Medium AF / TV AF
Focus control	
Iris control	Custom dial; Touchscreen; Auto
Aperture range	f1.8 - f8
Filter diameter	58mm
Lens elements/groups	12/10
Aperture blades	8 Blade Circular Aperture
Image stabilization system	Optical lens shift system (angle & vector movement detection) + electronic stabilisation; 4 modes: Intelligent (Auto), Dynamic, Standard, Powered Up to 400x;
Digital zoom	Built-in 2x Digital Teleconverter (cannot be used with Digital Zoom)
IMAGE PROCESSOR	
Type	DIGIC DV 4
RECORDING	
Video storage media	SDXC/SDHC/SD memory card (2 card slots); Dual Format recording, Double slot (simultaneous) recording and Relay (continuous) recording possible. ¹ Class 6 (or higher) cards recommended for 1080/50P recording;
Type	Class 4 (or higher) cards recommended for other Full HD recording
Recording time	128GB SDXC card: 10hrs 10mins (AVCHD max. quality) ¹ 8hrs 00mins (MP4 max. quality) ¹ 91hrs 55mins (MP4 lowest quality) ¹
Recording file format	AVCHD Progressive (v2.0, high profile); MP4
Recording format	AVCHD (all modes variable bit rate, 4:2:0 colour sampling); 1920x1080: 50p (28Mbps, linear PCM audio available); 1920x1080: 50i/PF25 (24Mbps, 17Mbps); 1440x1080: 50i/PF25 (5Mbps)
Slow/Fast motion	MP4 (all modes variable bit rate, 4:2:0 colour sampling); 1920x1080: 50p (35Mbps); 1920x1080: 25P (24Mbps, 17Mbps); 1280x720: 25P (4Mbps); 640x360: 25P (3Mbps) YES (MP4 HD mode only, x0.5/x2/x4/x10/x20/x60/x120/x1200
Interval Record	NO
Frame Record	NO
Pre Record (cache record)	YES (3 seconds)
Scan Reverse	NO
HD->SD conversion	NO
Internal Data Transfer	MOVIE & STILLs: Yes (card to card)
Photo storage media	SDXC/SDHC/SD memory card
Still quality	During video recording or playback: 1920 x 1080/1280 x 720/640 x 360

SYSTEM	
Monitoring Panel	
Type	Capacitive Organic LED
Size	8.77cm (3.5"), 100% view
Dots	1.23 million-dot equivalent
Touch Screen	Yes. Touch and Drag operations supported
Image quality adjustments	Brightness, backlight, OLED colour balance
Adjustable	YES (270 degree rotation about horizontal axis)
Waveform Monitor	NO
Focus Assist	Peaking; Magnifying
Peaking	YES
Zebra	YES (70% or 100% reference level)
Markers	ON/OFF (Level, Grid)
CVF	
Size	0.61cm (0.24"), 100% view
Dots	1.56 million dots equivalent
Adjustable	YES (tiltable to 45 degrees)
Correction lens	+ 2.0 to -5.5 diopter
INPUTS / OUTPUTS	
Audio In	XLR inputs with 48V phantom power (x2), 3.5mm microphone input jack
Headphone output	3.5mm stereo jack
Video monitor output	NO
HDMI	YES (HDMI™ mini connector, output only,
IEEE 1394 (Firewire)	NO
USB	YES (Mini-B, USB 2.0 Hi-Speed, output only)
HD/SD-SDI output	YES (576i, 720P or 1080i, output only, embedded audio and time code)
Time code	YES (Embedded in SDI output; superimposed on HDMI Output signal)
Genlock	NO
Component out	NO
AV terminal	3.5mm mini jack (output only for video and audio)
DC Input	YES
Remote Control Terminal	2.5mm mini jack
Colour Bars	YES (SMPTE or EBU), with 1KHz Tone
MISC	
Tally lamp	YES, in detachable handle
Accessory shoe	YES (cold shoe)
Custom key	YES (5 assignable buttons; select from 22 functions)
Custom Dial	YES (Shutter Priority (Tv), Aperture Priority (Av), Manual Exposure, exposure compensation, AGC limit)

no one sees it like you

Canon

Technical Specifications

XA35

SHOOTING FUNCTIONS	
EXPOSURE	
Exposure metering	Centre-weighted average or segment evaluative (determined by shooting mode); No metering: Fireworks mode, Fixed exposure (1/50 sec.)
Exposure compensation	-3 to +3 EV (12 steps); Backlight Correction available (Auto or always on)
Auto Exposure mode	Smart Auto, Face Detection AE; Manual control via Touch Exposure and Exposure Compensation functions
Exposure Lock	YES (via touchscreen)
Auto Gain Control setting	YES. Touch Exposure available
Auto Gain Control limit	Auto / Manual
ISO Sensitivity	0 to 24dB, 1dB increments (0 to 18dB in Cinema Mode)
Gain setting	0 to 24dB, 1dB increments (0 to 18dB in Cinema Mode)
SHUTTER SPEED	
Control Modes	Full Auto / Manual control (touchscreen LCD or control dial)
Shutter speed	1/6 to 1/2000 (depending on Scene Mode and frame rate)
Slow Shutter (SLS)	Yes. Auto On or Off
Clear Scan	NO
INFARED	
Infrared shooting mode	YES (green or white)
Built-in IR lamp	YES, in detachable handle
3D SHOOTING ASSIST	
OIS Axis Shift	NO
Focal Length Guide	NO
Shooting Modes	
Smart AUTO	YES
Program AE	AUTO: M mode: P, Tv, Av, M (manual exposure), SCN (Portrait, Sports, Snow, Beach, Sunset, Night, Low Light, Spotlight, Fireworks); Cinema mode: P, Tv, Av, M
Image Looks settings	Standard, Highlight Priority, Wide DR
Cinema Features	Cinema-Look Filter (9 options, including customisable 'Cinema Standard')
Image Effects	Brightness, Contrast, Sharpness, Colour Depth
Wi-Fi & GPS SPECIFICATIONS	
Wireless LAN standards	IEEE 802.11b/g/n/a(2.4GHz or 5GHz band) ²
Supported Wi-Fi Functions	Remote Operation; Movie Uploader (YouTube and Facebook ³); Playback (in browser); Media Server; FTP File Transfer
Supported Browser for Remote Operation	Internet Explorer 8 or later, Safari (iOS), Safari (MacOS), Android standard browser
Remote Operation Control Features	Aperture, Focus, WB, shutter Speed, Gain, Exposure Compensation, Shooting Mode, Slot select, Start/Stop Recording
Live view image Resolution	Camera setting mode: 680 x 383; Simplified setting: 284 x 160
Authentication Systems	Open/WPA-PSK/WPA2-PSK
Encryption	WEP64, WEP128, TKIP, AES
GPS Information (Optional Accessory)	Latitude/Longitude/Elevation, Coordinated Universal Time (UTC)

WHITE BALANCE	
Auto	YES
Preset	6: Daylight, Shade, Cloudy, Tungsten (incandescent lamps or halogen bulbs), Fluorescent H (3-wavelength type fluorescent), Fluorescent (white fluorescent)
Manual setting	Set 1, Set 2, Colour Temperature (2,000–15,000 K, 100K steps)
TIME CODE	
Countup system	Regen/Rec Run/Free Run/Preset (Non-Drop Frame)
Start value setting	"00:00:00.00", Set/Reset selectable
AUDIO	
Recording	AVCHD: Linear PCM ⁴ (2ch, 16 bit, 48 kHz) or Dolby Digital (AC-3 2ch, 48kHz) MP4: MPEG-2 AAC LC (2 ch)
Control	Audio controls include: Independent 2ch Line/Mic/Mic+48V input; Independent level control per channel (-∞ to +18 dB); Independent audio limiters (2 ch); Input mic trimming
Microphone attenuation	Auto/On/Off (20dB)
Microphone level meter	YES
Wind Screen	YES
Zoom Microphone	YES (customisable frequency response and directivity)
ACCESSORIES	
Supplied	Lens hood with barrier, Mic holder unit, Handle unit (HDU-I), Wireless Controller (WL-D89), Battery Pack BP-820, High Speed HDMI Cable (HTC100/S), Compact Power unit CA-570, AC Cable, Interface Cable (IFC-300PCU/S), Stereo Video Cable (STV-250N), PIXELA Data Import Utility Ver2.0
Optional	Canon Battery Pack BP-820/BP-828 Canon Compact Power Adapter CA-570, Canon Battery Charger CG-800E/CG-800B, Canon HDMI cable HTC-100, Canon Stereo Video Cable STV-250N, Canon Tele Converter TL-H58, Canon Wide Attachment WA-H58, Canon Wireless Microphone WM-V1, Canon Soft Carrying Case SC-1000, SC-2000, Wrist Strap, WS-20, Canon PROTECT Filter 58 mm, Canon ND4-L Filter 58 mm, Canon ND8-L Filter 58 mm, Canon GPS Receiver GP-E2, Canon Battery Video Light VL-10Li/VL-10LiIII (Model A/B only), Canon Battery Pack BP-900 series (for VL-10Li/VL-10LiIII), Canon Compact Power Adapter CA-910/920/930 (for charging BP-900 series)
Backup power supply	Lithium coin battery (built-in)
Power Consumption	Max Approx. 5.2W ⁵ (AVCHD) / 5.1W (MP4) ⁵
Continuous Recording Time	Supplied BP-820: Approx. 145 minutes ⁵ Optional BP-828: Approx. 220 minutes ⁵
MISCELLANEOUS	
Dimensions	Approx. 109 x 84 x 182 mm (main body only) Approx. 131 x 180 x 231 mm (fully equipped)
Detachable handle	YES
Weight (camera only)	Approx. 770 g
	Approx. 1160 g
Weight (fully equipped)	
Operating Temperature range	-5 to +45°C, 60% relative humidity 0°C to +40°C, 80% relative humidity

All data is based on Canon standard testing methods except where indicated.

- After 12 hours of continuous recording, camcorder will stop recording and re-start automatically. Simultaneous/Dual Format recording not available in 1080/50P modes.
- 5Ghz not available in Qatar; capability and functionality may vary by region
- iOS devices only, excludes MP4 1080/50P mode
- AVCHD 1080/50P mode only
- 28Mbps / 35Mbps recording, normal EVF brightness

All specifications are subject to change without notice

For more information visit
canon.com.au
canon.co.nz

no one sees it like you

Canon